

Product Data Sheet

DIN 41612 straight spring-loaded connector (Female), straight type, E,
Part No. 108-40074






Illustration similar



Parallel



Perpendicular



Through Hole



Power



Rugged

- tail length 4.6 mm
- Connection 0.6 x 0.6
- number of positions: 48
- solder termination
- performance level 2



» to product on www.ept.de



» to product group DIN 41612

Product Data Sheet

DIN 41612 straight spring-loaded connector (Female), straight type, E,
Part No. 108-40074



Technical Specifications

Basics

Specification	IEC 60603-2 (DIN 41612)
Performance Level	2
No. of Contacts	48
Termination Technology	solder termination
Termination Length	4.6 mm
Board-to-Board Distance	17.85 mm
Operating Temperature Range	-55°C to +125°C

Material

Insulator Material	glass-fiber reinforced PBT, UL 94 V-0
CTI value <i>IEC 60112</i>	200
Contact Material	copper alloy

Mechanical

Pitch	5.08 mm
Mating Force	60 N
Separating Force per Pin	> 0.15 N
Durability	400 mating cycles

Electrical

Operational Current	5.6 A
Test Voltage	1500 V
Contact Resistance	15 mΩ
Clearance and Creepage	≥ 3.0 mm
Insulation Resistance	> 10 ⁶ MΩ

Processing

Soldering Temperature	up to 260°C
-----------------------	-------------

Approval / Compliance

UL file	E130314
Environment	RoHS compliant

Product Data Sheet

DIN 41612 straight spring-loaded connector (Female), straight type, E,
Part No. 108-40074



Derating Diagram



Product Data Sheet

DIN 41612 straight spring-loaded connector (Female), straight type, E,
Part No. 108-40074



Options

Board Lock

Suitable for connectors with type B, C, D, E, F low profile, G low profile, M female connectors and R male connectors



	Forces			Part Number	PCB Thickness
Type of Insertion	F_m	not soldered F_h	soldered F_h	108-40074C1	1.6 mm
Locked	< 20 N	> 10 N	> 25 N	108-40074C2	2.4 mm
Under Tension	< 20 N	> 5 N	> 25 N	108-40074C3	3.6 mm

Modifications

Available on request

- without mounting flange
- Special lengths for connections
- Grade I + III or custom
- custom loading

Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)