

# Product Data Sheet

DIN 41612 Shroud C/R,  
Part No. 115-15302

---



Illustration similar



Perpendicular

- for PCB thickness 3.2 mm
- for post length 17 mm
- C/R



» to product on [www.ept.de](http://www.ept.de)



» to product group DIN 41612

# Product Data Sheet

DIN 41612 Shroud C/R,  
Part No. 115-15302



## Technical Specifications

### Basics

|                             |                         |
|-----------------------------|-------------------------|
| Specification               | IEC 60603-2 (DIN 41612) |
| Operating Temperature Range | -55°C to +125°C         |

### Material

|                    |                                       |
|--------------------|---------------------------------------|
| Insulator Material | glass-fiber reinforced PBT, UL 94 V-0 |
|--------------------|---------------------------------------|

### Mechanical

|       |         |
|-------|---------|
| Pitch | 2.54 mm |
|-------|---------|

### Approval / Compliance

|             |                |
|-------------|----------------|
| Environment | RoHS compliant |
|-------------|----------------|

# Product Data Sheet

DIN 41612 Shroud C/R,  
Part No. 115-15302

---



## Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)