

Product Data Sheet

DIN 41612 straight Female, type B,
Part No. 302-40064-05TH





Illustration similar



Parallel



Perpendicular



Through Hole



Rugged

- tail length 2.5 mm
- number of positions: 64
- THR
- performance level 2



» to product on www.ept.de



» to product group DIN 41612

Product Data Sheet

DIN 41612 straight Female, type B,
Part No. 302-40064-05TH



Technical Specifications

Basics

Specification	IEC 60603-2 (DIN 41612)
Performance Level	2
No. of Contacts	64
Termination Technology	THR
Termination Length	2.5 mm
Board-to-Board Distance	16.85 mm
Operating Temperature Range	-55°C to +125°C

Material

Insulator Material	glass-fiber reinforced PA, UL 94 V-0
CTI value <i>IEC 60112</i>	600
Contact Material	copper alloy

Mechanical

Pitch	2.54 mm
Mating Force	60 N
Separating Force per Pin	> 0.15 N
Durability	400 mating cycles

Electrical

Operational Current	2.6 A
Test Voltage	1000 V
Contact Resistance	20 mΩ
Clearance and Creepage	≥ 1.2 mm
Insulation Resistance	> 10 ⁶ MΩ

Processing

Soldering Temperature	260°C according to J-STD-020
MSL	1

Approval / Compliance


UL file	E130314
Environment	RoHS compliant

Product Data Sheet

DIN 41612 straight Female, type B,
Part No. 302-40064-05TH



Derating Diagram



Product Data Sheet

DIN 41612 straight Female, type B, Part No. 302-40064-05TH



Options

Board Lock

Suitable for connectors with type B, C, D, E, F low profile, G low profile, M female connectors and R male connectors



	Forces			Part Number	PCB Thickness
Type of Insertion	F_m	not soldered F_h	soldered F_h	302-40064-05THC 1	1.6 mm
Locked	< 20 N	> 10 N	> 25 N	302-40064-05THC 2	2.4 mm
Under Tension	< 20 N	> 5 N	> 25 N	302-40064-05THC 3	3.6 mm

Modifications

Available on request

- without mounting flange
- Special lengths for connections
- Grade I + III or custom
- custom loading

Accessories

» DIN 41612 keying, type B and C
Part Number 104-19003

Product Data Sheet

DIN 41612 straight Female, type B,
Part No. 302-40064-05TH



Drawings

Component data in 2D and 3D format you can download here:

» [PDF](#)