

Product Data Sheet

Zero8 plug mid-profile geschirmt,
Part No. 405-53112-51





Illustration similar



Parallel



SMT



High Density



High Speed



Rugged



EMC

- Bauhöhe 2.65 mm
- Kontaktüberdeckung 1.5 mm
- Polzahl 12 im Raster 0.8 mm
- Anschlusstechnik SMT
- EMV-Schirmung
- Performance level 1



» to product on www.ept.de



» to product group Zero8

Product Data Sheet

Zero8 plug mid-profile geschirmt, Part No. 405-53112-51



Technical Specifications

Basics

Performance Level <i>IEC 60512-9-1:2010</i>	1
No. of Contacts	12
Termination Technology	SMT
Board-to-Board Distance	7.5 mm bis 15.0 mm
Operating Temperature Range	-55°C bis + 125°C

Material

Insulator Material	LCP, UL 94 V-0
CTI value <i>IEC 60112</i>	150
Contact Material	Kupferlegierung
Plating	Au über Ni
Termination area	Sn über Ni

Mechanical

Pitch	0.8 mm
Mating Force per Pin	≤ 0.5 N
Separating Force per Pin	≤ 0.4 N
Durability <i>IEC 60512-9-1</i>	500 Steckzyklen
Coplanarity	≤ 0.1 mm
Vibration, sinusoidal <i>IEC 60512-6-4</i>	10 - 2000 Hz, 20g
Contact mating problems if vibrations occur, sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μ s
Shock, semi-sinusoidal <i>IEC 60512-6-3</i>	50g, 11 ms
Contact mating problems if shock occur, semi-sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μ s
Overmating Distance	0.8 mm
Wipe length	1.5 mm
Center offset	± 0.7 mm
Axial offset when mated (x/y)	± 0.4 mm
Angular offset	$\pm 5^\circ$

Product Data Sheet

Zero8 plug mid-profile geschirmt,
Part No. 405-53112-51



Technical Specifications

Electrical

Operational Current <i>IEC 60512-5-2</i>	1.7 A pro Pin bei 20°C (80 von 80 Pins bestromt) 5.5 A pro Pin bei 20°C (2 von 80 Pins bestromt) 5.1 A pro Pin bei 20°C (4 von 80 Pins bestromt) 16 A bei 20°C (Schirm bestromt)
Test Voltage <i>IEC 60512-4-1</i>	500 VAC
Contact Resistance <i>IEC 60512-2-1</i>	$\leq 20 \text{ m}\Omega$
Clearance and Creepage	0.25 mm
Insulation Resistance <i>IEC 60512-3-1</i>	$> 5 \text{ G}\Omega$
Data Transfer Rate	16 Gbit/s

Processing

Soldering Temperature <i>JEDEC J-STD-020E</i>	20 - 40 s bei 260°C
MSL <i>JEDEC J-STD-020E</i>	1
Assembly	Pick and Place

Approval / Compliance


UL file	E130314
Environment	RoHS konform

Product Data Sheet

Zero8 plug mid-profile geschirmt,
Part No. 405-53112-51



Derating Diagram



Product Data Sheet

Zero8 plug mid-profile geschirmt,
Part No. 405-53112-51



Modifications

Available on request

- andere Polzahlen
- andere Gütestufen

Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)