

Product Data Sheet

Zero8 socket low-profile ungeschirmt,
Part No. 406-52080-51





Illustration similar



Parallel



SMT



High Density



High Speed



Rugged

- Bauhöhe 4.85 mm
- Kontaktüberdeckung 1.5 mm
- Polzahl 80
- Anschlusstechnik SMT
- Raster 0.8 mm
- Performance level 1



» to product on www.ept.de



» to product group Zero8

Product Data Sheet

Zero8 socket low-profile ungeschirmt, Part No. 406-52080-51



Technical Specifications

Basics

Performance Level <i>IEC 60512-9-1:2010</i>	1
No. of Contacts	80
Termination Technology	SMT
Board-to-Board Distance	6.0 mm bis 15.0 mm
Operating Temperature Range	-55°C bis + 125°C

Material

Insulator Material	LCP, UL 94 V-0
CTI value <i>IEC 60112</i>	150
Contact Material	Kupferlegierung
Plating	Au über Ni
Termination area	Sn über Ni

Mechanical

Pitch	0.8 mm
Mating Force per Pin	≤ 0.5 N
Separating Force per Pin	≤ 0.4 N
Durability <i>IEC 60512-9-1</i>	500 Steckzyklen
Coplanarity	≤ 0.1 mm
Vibration, sinusoidal <i>IEC 60512-6-4</i>	10 - 2000 Hz, 20g
Contact mating problems if vibrations occur, sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μ s
Shock, semi-sinusoidal <i>IEC 60512-6-3</i>	50g, 11 ms
Contact mating problems if shock occur, semi-sinusoidal <i>IEC 60512-2-5</i>	≤ 1 μ s
Overmating Distance	0.8 mm
Wipe lenght	1.5 mm
Center offset	± 0.7 mm
Axial offset when mated (x/y)	± 0.4 mm
Angular offset	$\pm 5^\circ$

Product Data Sheet

Zero8 socket low-profile ungeschirmt,
Part No. 406-52080-51



Technical Specifications

Electrical

Operational Current <i>IEC 60512-5-2</i>	1.7 A pro Pin bei 20°C (80 von 80 Pins bestromt) 5.5 A pro Pin bei 20°C (2 von 80 Pins bestromt) 5.1 A pro Pin bei 20°C (4 von 80 Pins bestromt)
Test Voltage <i>IEC 60512-4-1</i>	500 VAC
Contact Resistance <i>IEC 60512-2-1</i>	≤ 20 mΩ
Clearance and Creepage	0.25 mm
Insulation Resistance <i>IEC 60512-3-1</i>	> 5 GΩ
Data Transfer Rate	16 Gbit/s

Processing

Soldering Temperature <i>JEDEC J-STD-020E</i>	20 - 40 s bei 260°C
MSL <i>JEDEC J-STD-020E</i>	1
Assembly	Pick and Place

Approval / Compliance


UL file	E130314
Environment	RoHS konform

Product Data Sheet

Zero8 socket low-profile ungeschirmt,
Part No. 406-52080-51



Derating Diagram



Product Data Sheet

Zero8 socket low-profile ungeschirmt,
Part No. 406-52080-51



Modifications

Available on request

- andere Polzahlen
- andere Gütestufen

Drawings

Component data in 2D and 3D format you can download here:

[» PDF](#)

[» 3D IGES](#)

[» 3D STEP](#)

[» 3D PDF](#)